



ALUSOLVE

Aluminum cleaner

DESCRIPTION

ALUSOLVE is a very powerful aluminium cleaner. The ALUSOLVE is ideal on ferrous metals or nonferrous metals. It removes oxydation film, corrosion and dirt on aluminium plates in only one step. ALUSOLVE is ideal to clean aluminium trailer's and trucks.

ADVANTAGES

- 1. Safe for septic tank
- 2. Instantly removes oxidation, corrosion & dirt stains



TECHNICAL DATA

pH (as is)	1.0 (Très Acide)
Density (20°C)	1.15 g/cc
Colour	Clear
Fragrance	
Characteristic	
Biodegradability	
Flash Point	More than 95°C
Freezing Stability	
Degradability determined in accordance with OECD no. 301D.	

DIRECTIONS

DIRECTIONS: DO NOT USE ON NEW EQUIPMENT.

- 1. Wet the surface to clean with water.
- 2. Spray ALUSOLVE on the surface.
- 3. Leave the solution to act 5 minutes and rinse with water.
- 4. In order to clean the rusted and scaled areas, spray ALUSOLVE with a rigid brush.

DILUTIONS:

Normal cleaning:

Dilute 1 part of cleaner in 10 parts of water. To apply with brush or sponge.

For cleaning plates before welding:

Mix 1 part of cleaner in 2 parts of water. Apply with brush. Let it work for 2 minutes and then dry. No rinsing requested.

WARNING: Avoid all lengthen contact with glass.