

CRL 50

STANDARD EQUIPMENT



0.968.0005



0.968.0006

AVAILABLE IN 2 VERSIONS

+ 3.554.0051
With electric motor
MNF 230V 50 Hz



+ 3.554.0052
With internal
combustion engine
**Loncin LC148F-
2S BA**

OPTIONAL



Optional:

- 0.966.0065 ABS Hose reel (hose not included)
- 0.966.0068 ABS Hose reel hose included 20 m
- 0.966.0070 ABS Hose reel hose included 50 m

Equipped with:


- Tank in high strength polyethylene
- Very low barycentre that guarantees stability
- Complete emptying even on ground that is not perfectly flat
- Lever spray gun with nozzle and diffuser
- External filter
- Tubular frame with detachable handles
- Frame support foot part of the frame, not removable
- **Optional** hose reel on request

Both codes needs to be ordered to receive the finished product

	CRL 50 with electric motor	CRL 50 with internal combustion engine
code	0.068.0001 + 3.554.0051	0.068.0001 + 3.554.0052
operat. pressure	20 bar-2900 psi	20 bar-2900 psi
delivery rate	1200 l/h-5.55 GPM	1200 l/h-5.55 GPM
power	Electric motor 230V ~ 50Hz	Engine Loncin LC148F-2S BA
solution tank capacity	50 lt.	50 lt.
high pressure hose	5 m.	5 m.

CRL 80

STANDARD EQUIPMENT



AVAILABLE IN 2 VERSIONS

+ 3.554.0051
With electric motor
MNF 230V 50 Hz



+ 3.554.0052
With internal
combustion engine
**Loncin LC148F-
2S BA**

OPTIONAL



Optional:

- 0.966.0066 ABS Hose reel (hose not included)
- 0.966.0074 Sheet metal hose reel (hose not included)
- 0.966.0069 ABS Hose reel hose included 20 m
- 0.966.0071 ABS Hose reel hose included 40 m

Equipped with:

- Tank in high strength polyethylene
- Very low barycentre that guarantees stability
- Complete emptying even on ground that is not perfectly flat
- Lever spray gun with nozzle and diffuser
- External filter
- Tubular frame with detachable handles
- Frame support foot part of the frame, not removable
- **Optional** hose reel on request

Both codes needs to be ordered to receive the finished product

	CRL 80 with electric motor	CRL 80 with internal combustion engine
code	0.068.0002 + 3.554.0051	0.068.0002 + 3.554.0052
operat. pressure	20 bar-2900 psi	20 bar-2900 psi
delivery rate	1200 l/h-5.55 GPM	1200 l/h-5.55 GPM
power	Electric motor 230V ~ 50Hz	Engine Loncin LC148F-2S BA
solution tank capacity	80 lt.	80 lt.
high pressure hose	10 m.	10 m.

CRL 120

STANDARD EQUIPMENT



0.968.0005



0.968.0007

AVAILABLE IN 2 VERSIONS

+ 3.554.0051
With electric motor
MNF 230V 50 Hz



+ 3.554.0052
With internal
combustion engine
**Loncin LC148F-
2S BA**

OPTIONAL



Optional:

- 0.966.0067 ABS Hose reel (hose not included)
- 0.966.0075 Sheet metal hose reel (hose not included)
- 0.966.0072 ABS Hose reel hose included 20 m
- 0.966.0073 ABS Hose reel hose included 40 m

Equipped with:

- Tank in high strength polyethylene
- Very low barycentre that guarantees stability
- Complete emptying even on ground that is not perfectly flat
- Lever spray gun with nozzle and diffuser
- External filter
- Tubular frame with detachable handles
- Frame support foot part of the frame, not removable
- **Optional** hose reel on request

Both codes needs to be ordered to receive the finished product

	CRL 120 with electric motor	CRL 120 with internal combustion engine
code	0.068.0003 + 3.554.0051	0.068.0003 + 3.554.0052
operat. pressure	20 bar-2900 psi	20 bar-2900 psi
delivery rate	1200 l/h-5.55 GPM	1200 l/h-5.55 GPM
power	Electric motor 230V ~ 50Hz	Engine Loncin LC148F-2S BA
solution tank capacity	120 lt.	120 lt.
high pressure hose	10 m.	10 m.