

Dart



LEVEL




CHARGER



STOP



NEW



LI-ION BATTERY

Model: Dart 38B Li

STANDARD EQUIPMENT



* 5.511.2262
PP brush Ø 380 mm - 15"
(38 B Li)

5.511.2213
PP brush Ø 360 mm - 14"
(36 B- 36 E)



4.508.1100
Front squeegee blade
L.537 mm - Th. 1,5 mm
4.508.1101
Rear squeegee blade
L.590 mm - Th. 3,0 mm



0.108.0076
On-board Battery charger
24V-5A
only for model code:
8.581.0002
8.581.0003



0.108.0089 On-board Battery charger
29,4V 12A 110-230V
50/60Hz
only for model code:
8.581.0022



2x 0.107.0083
AGM NP3312 12 V 33 Ah
C20/28 Ah C5 (only for
model code: 8.581.0003)



1x 0.107.0091
Li-ion battery 24V 30Ah
700Wh
only for model code:
8.581.0022

Equipped with:

- Ideal for small and medium floors up to 1260 sqm, especially when congested by people or furnishing like in wellness centres, gyms, car showroom, retail shops, hospitals and schools.
- **Li-ion battery 24V** (38B Li)
- Automatic brush attachment, discharge and delayed cut-off.
- Narrow body with both side brush protrusion and 300° squeegee spin.
- Tool less removable recovery tank with large visual inspection window and stretchable discharge hose.
- Adjustable driving handle with dead man switches, soft touch controls and diagnosis (Eco Energy mode and battery low level automatic cut-off for DC version).
- Clean water tank level indicator
- Large non marking working wheels and sturdy rear roller for displacements.

*** New, standard on machines starting from 2022, compatible with all previous machine models**

	Dart 36E	Dart 36B	Dart 36B	Dart 38B Li
code	8.581.0001	8.581.0002	8.581.0003	8.581.0022
power supply	220/240 V 50/60Hz	24V (battery charger included)	24V (batteries and charger included)	24V (Li-ion battery and charger included)
scrubbing/squeegee width	360/460 mm	360/460 mm	360/460 mm	380/460 mm
max working capacity	1260 m ² /h	1260 m ² /h	1260 m ² /h	1350 m ² /h
solution tank capacity	15 l/3.96 gal	15 l/3.96 gal	15 l/3.96 gal	15 l/3.96 gal
recovery tank capacity	16 l/4.23 gal	16 l/4.23 gal	16 l/4.23 gal	16 l/4.23 gal
traction	mechanical	mechanical	mechanical	mechanical
RPM/pressure on the brush	130/18 kg/40 lbs	160/27 kg/60 lbs	160/27 kg/60 lbs	160/27 kg/60 lbs
brush motor power	300 W	400 W	400 W	400 W
detergent solution system	solenoid valve	solenoid valve	solenoid valve	solenoid valve
depression/vacuum motor	850 mmH ₂ O/350 W	850 mmH ₂ O/270 W	850 mmH ₂ O/270 W	850 mmH ₂ O/270 W
dimensions/weight	98x47x99 cm/57 kg	98x47x99 cm/46 kg	98x47x99 cm/70 kg	98x47x99 cm/63 kg



On/off switch protecting unintentional use. Protection against overloads, battery discharge abuse (DC only) and undesired run. Convenient one switch maintenance over the brush. Eco Energy setting for extensive working time and extremely quiet operations (DC only).

Accessible on-board charger (DC only, when provided), far away from sprays. Time saving convenient foot operating squeegee lift. Handle can be easily adjusted to fit comfort of operators even in narrow spaces.



Easy access and handling to clean recovery tank and floater. Less downtimes due to simple maintenance and construction. Great visibility and cleaning capability on hard to reach edges on both sides of the brush.




Extensive squeegee spin for easy blade replacement and perfect suction even on corners. Easy setting and automatic solution release to save chemical and fit different floor conditions. High stability and capability to overtake small steps.





OPTIONAL

- * 
 - 5.511.2214 Tynex brush Ø 360 mm-14"
 - 5.511.2215 PP 0,3 brush Ø 360 mm-14"
 - 5.511.2216 PES brush Ø 360 mm - 14"

- 5.511.2264 Tynex brush Ø 380 mm-15"
- 5.511.2265 PP 0,3 brush Ø 380 mm-15"
- 5.511.2266 PES brush Ø 380 mm - 15"

- 
 - 4.508.1058 Polyurethane front blade L.537
 - 4.508.1059 Polyurethane rear blade L.590

- * 
 - 5.511.2217 EWU pad driver Ø 360 mm-14"

- 
 - 6.508.0143 Abrasive pad Ø 381 mm-15" - beige
 - 6.508.0144 Abrasive pad Ø 381 mm-15" - green
 - 6.508.0141 Abrasive pad Ø 381 mm-15" - black

- 
 - 4.512.0068 Extension electric cord 15 m with Schuko plug (Dart 36 E)