

## Next Evo

### LEVEL



### CHARGER



### STOP



### STANDARD EQUIPMENT



**Next Evo 55**  
• 5.511.2243  
PP brush Ø 533 mm - 21"



**Next Evo 66**  
• 2 x 5.511.2212  
PP brush Ø 330 mm - 13"



**Next Evo 55**  
• 4.508.X468  
Front squeegee blade L.830 mm  
Shore 40 Th. 2.5 mm  
• 4.508.X467  
Rear squeegee blade L.870 mm  
Shore 40 Th. 3 mm

**Next Evo 66**  
• 4.508.1524  
Front squeegee blade L.860 mm  
Shore 33 Th. 4 mm  
• 4.508.1523  
Rear squeegee blade L.900 mm  
Shore 40 Th. 4 mm



• 0.108.0059  
On-board Battery charger  
24V 12A  
only for model code:  
8.525.1301  
8.525.1302

### Equipped with:

- Designed for the maintenance and deep cleaning of large areas (up to 1.700 m<sup>2</sup>)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- User friendly control panel
- Hour meter
- Automatic brush lifting (model 66BTA only)
- Fully accessible recovery water tank with visual inspection
- Automatic detergent measuring system
- Big size traction wheels
- Handle with control lever.

**\* New, standard on machines starting from 2022, compatible with all previous machine models**

	Next Evo 55BT	Next Evo 55BT	Next Evo 66BTA	Next Evo 66BTA
code	8.525.1312	8.525.1301	8.525.1313	8.525.1302
power supply	24V	24V (battery charger included)	24V	24V (battery charger included)
scrubbing/squeegee width	550/800 mm	550/800 mm	660/800 mm	660/800 mm
max working capacity	2200 m <sup>2</sup> /h	2200 m <sup>2</sup> /h	2640 m <sup>2</sup> /h	2640 m <sup>2</sup> /h
solution tank capacity	55 l/14.5 gal	55 l/14.5 gal	55 l/14.5 gal	55 l/14.5 gal
recovery tank capacity	55-65 l/14.52-17.17 gal	55-65 l/14.52-17.17 gal	55-65 l/14.52-17.17 gal	55-65 l/14.52-17.17 gal
traction/traction motor	automatic/200W	automatic/200W	automatic/200W	automatic/200W
RPM/pressure on the brushes	165/30 kg/66 lbs	165/30 kg/66 lbs	175/33 kg/72 lbs	175/33 kg/72 lbs
brush motor power	550 W	550 W	2 x 400 W	2 x 400 W
detergent solution system	solenoid valve	solenoid valve	solenoid valve	solenoid valve
depression/vacuum motor	1200 mmH <sub>2</sub> O/400 W	1200 mmH <sub>2</sub> O/400 W	1200 mmH <sub>2</sub> O/400 W	1200 mmH <sub>2</sub> O/400 W
dimensions/weight	128x71x106 cm/106 kg	128x71x106 cm/106 kg	128x71x106 cm/110 kg	128x71x106 cm/110 kg

**OPTIONAL**



User friendly analogic control panel. Control lever for brush operation and detergent water outflow. ON/OFF and battery cutout key switch, brush and vacuum motor switch, detergent regulation device. Thermal circuit breaker to protect vacuum motor and brush motor, battery charge level indicator. Hour meter, clean water tank



- 2 x 0.107.0002 Tubular battery Pb-acid 12V 118Ah C5



- 2 x 0.107.0063 GEL Battery 12 MFP 105 12V 105Ah C5




- 0.108.0078 Battery Charger 24V 13A 220-240/50-60



- 4.508.1178 Polyurethane front blade L.830 TH. 3
- 4.508.1177 Polyurethane rear blade L.870 TH. 3
- 4.508.1526 Polyurethane front blade L.860 TH. 2
- 4.508.1525 Polyurethane rear blade L.900 TH. 3



- \* • 5.511.2244 Tynex brush Ø 533 mm-21"
- 2x 5.511.2208 Tynex brush Ø 330 mm-13" 2x
- 5.511.2245 PP brush Ø 533 mm-21"
- 2x 5.511.2209 PP 0,3 brush Ø 330 mm-13" 2x
- 5.511.2246 PES brush Ø 533 mm-21"
- 2x 5.511.2210 PES brush Ø 330 mm-13" 2x



- \* • 5.511.2247 EWU pad driver Ø 533mm-21"
- 2x 5.511.2211 EWU pad driver Ø 330mm-13"

level indicator. Detergent regulation device. Recovery tank drain hose with adjustable flow system. Automatic brush lifting (only model 66BTA).



Automatic detergent dosing system (only for model code: 8.525.1301 - 8.525.1302) Fully accessible recovery water tank with visual inspection. Easy access to the recovery tank. Easy access and simple service of the components without use of tools.

Battery trolley for a quick and easy battery change (only for model code: 8.525.1301 - 8.525.1302). Big size wheels for better maneuverability and effortless use.



- (5 pcs package)
- 6.508.0035 - Ø 533 mm-21"- beige
  - 6.508.0042 - Ø 533 mm-21"- green
  - 6.508.0049 - Ø 533 mm-21"- black
  - 6.508.0030 - Ø 340 mm-13"- beige
  - 6.508.0037 - Ø 340 mm-13"- green
  - 6.508.0044 - Ø 340 mm-13"- black